



مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
1 DH-HAC-HFW2802TP-Z-A	4K Starlight HDCVI IR Bullet Camera, 1/2" Progressive Scan CMOS 15fps@4K, 20fps@6MP, 25/30fps@4MP 3.7-11mm motorized lens, Max Aperture: F1.5 WDR(120dB), Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR HD/SD switchable, 1CH Audio In, built-in mic Max. IR length 80m, Smart IR, IP67, DC12V±30%		22,000,000
2 DH-HAC-HFW2802TP-A-I8	4K Starlight HDCVI IR Bullet Camera, 1/2" Progressive Scan CMOS 15fps@4K, 20fps@6MP, 25/30fps@4MP 3.6mm fixed lens, Max Aperture: F1.6 WDR(120dB), Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR HD/SD switchable, 1CH Audio In, built-in mic Max. IR length 80m, Smart IR, IP67, DC12V±30%		15,000,000
3 DH-HAC-HFW2802EP-A	4K Starlight HDCVI IR Bullet Camera, 1/2" Progressive Scan CMOS 15fps@4K, 20fps@6MP, 25/30fps@4MP, 3.6mm fixed lens WDR(120dB), Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR HD/SD switchable, 1CH Audio In, built-in mic Max. IR length 40m, Smart IR, IP67, DC12V±30%		12,500,000
4 DH-HAC-HFW2601TP-Z-A	6MP WDR HDCVI IR Bullet Camera, 1/2.9" Progressive Scan CMOS 20fps@6MP, 25/30fps@4MP 2.7-13.5mm motorized lens, Max Aperture: F1.3 WDR(120dB), Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR HD/SD switchable, 1CH Audio In, built-in mic Max. IR length 80m, Smart IR, IP67, DC12V±30%		17,500,000
5 DH-HAC-HFW2601EP-A	6MP WDR HDCVI IR Bullet Camera, 1/2.9" Progressive Scan CMOS 20fps@6MP, 25/30fps@4MP, 3.6mm fixed lens, Aperture: F1.9 WDR(120dB), Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR HD/SD switchable, 1CH Audio In, built-in mic Max. IR length 40m, Smart IR, IP67, DC12V±30%		12,000,000
6 DH-HAC-HFW1500THP-I4	5MP HDCVI IR Bullet Camera, 1/2.7" Progressive Scan CMOS 20fps@5MP, 25/30fps@4MP, 3.6mm fixed lens, Aperture: F1.85 DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Support Electronic Defog, HD/SD switchable Max. IR length 40m, Smart IR, IP67, DC12V±30%		7,550,000
7 HAC-B1A51	5MP HDCVI IR Bullet Camera, 1/2.7" 5 MegaPixel CMOS 20fps@5MP, 25/30fps@4MP, 25/30@1080P 3.6mm, 2.8mm fixed lens, HD and SD output switchable DWDR, Day/Night(ICR), BLC, HLC, AGC, AWB, 2D-DNR, Support OSD Menu, Max. IR length 20m, Smart IR, IP67, DC12V, Casing Plastic		5,200,000
8 DH-HAC-B2A51P	5MP HDCVI IR Bullet Camera, 1/2.7" 5 MegaPixel CMOS 20fps@5MP, 25/30fps@4MP, 25/30@1080P 3.6mm fixed lens, HD and SD output switchable DWDR, Day/Night(ICR), BLC, HLC, AGC, AWB, 2D-DNR, Support OSD Menu, Max. IR length 20m, Smart IR IP67, DC12V, Casing Aluminium		5,900,000
9 DH-HAC-HFW1400RP-VF-IRE6	1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 2.7-13.5mm vari-focal lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable, OSD Menu Max. IR length 60m, Smart IR, IP67, DC12V		10,500,000
10 DH-HAC-HFW1400DP	1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens, HD and SD output switchable DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR OSD Menu, Max. IR length 80m, Smart IR, IP67, DC12V		8,300,000
11 DH-HAC-HFW1400BP	1/3" 4Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens, HD and SD output switchable DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR OSD Menu, Max. IR length 50m, Smart IR, IP67, DC12V		7,600,000

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
12	DH-HAC-HFW1400SP 1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens, HD and SD output switchable DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR OSD Menu, Max. IR length 30m, Smart IR, IP67, DC12V		6,500,000
13	DH-HAC-HFW1400SLP 4MP HDCVI IR Bullet Camera 1/2.7" 4Megapixel CMOS, 25/30fps@4MP, 25/30fps@1080P 3.6mm Fixed Lens, HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR, IP67, DC12V		5,900,000
	<b>NEW Product</b>		
14	DH-HAC-HFW1400TP 4MP HDCVI IR Bullet Camera, 1/2.7" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 3.6mm & 2.8mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable, OSD Menu Max. IR length 30m, Smart IR, IP67, DC12V		6,350,000
15	DH-HAC-HFW1400TP-A 4MP HDCVI IR Bullet Camera, 1/2.7" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 3.6mm & 2.8mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable, Built in mic, OSD Menu Max. IR length 30m, Smart IR, IP67, DC12V		6,700,000
	<b>NEW Product</b>		
16	DH-HAC-ME1400B-PIR 4MP HDCVI MotionEye Camera, 1/3" 4.1Megapixel CMOS 25/30fps@4MP & @1080P & @720P, 2.8mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR 10m/110°detecting range/angle, HD and SD output switchable OSD Menu, Max. IR length 20m, Smart IR, IP67, DC12V		7,000,000
	<b>Cooper Series</b>		
17	DH-HAC-B1A41P 4MP HDCVI IR Bullet Camera, 1/2.7" 4Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 3.6mm fixed lens HD and SD output switchable, Max. IR length 20m IP67, DC12V, Casing: Plastic		4,700,000
	<b>Cooper Series</b>		
18	DH-HAC-B2A41P 4MP HDCVI IR Bullet Camera, 1/2.7" 4Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 3.6mm fixed lens HD and SD output switchable, Max. IR length 20m IP67, DC12V, Casing: Aluminium		5,400,000
19	DH-HAC-HFW1230TP 2MP Starlight HDCVI IR Bullet Camera, 1/2.8" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens (2.8mm, 6mm Optional) HD and SD output switchable, Support OSD Menu Starlight, DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR, IP67, DC12V, Casing: Aluminium		5,400,000
	<b>NEW Product</b>		
20	DH-HAC-HFW1230TP-A 2MP Starlight HDCVI IR Bullet Camera, 1/2.8" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 3.6mm fixed lens HD and SD output switchable, Built-in mic DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR, IP67, DC12V		5,800,000
	<b>NEW Product</b>		
21	DH-HAC-HFW1230DP 1/2.8" 2Megapixel CMOS (Starlight) 3.6mm Fixed lens, 25/30fps@1080P & @720P DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable, OSD Menu Max. IR length 80m, Smart IR, IP67, DC12V		7,200,000
22	DH-HAC-HFW1220TLP 2MP Value Starlight HDCVI IR Bullet Camera 1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 3.6mm Fixed Lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 40m, Smart IR, IP67, DC12V		4,400,000
	<b>NEW Product</b>		
23	DH-HAC-HFW1220RP-VF-IRE6 1/2.9" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 2.7-12mm vari-focal lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 60m, Smart IR, IP67, DC12V		8,900,000
24	DH-HAC-HFW1220DP 1/2.9" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 3.6mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 80m, Smart IR, IP67, DC12V		6,200,000
25	DH-HAC-HFW1220SP 1/2.9" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 3.6mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR, IP67, DC12V		4,500,000
















**توجه:** دستگاه های جدید XVR (به جز دستگاه های ستاره دار)، دوربین هایی که میکروفن داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
26	DH-HAC-HFW1200TLP <b>NEW Product</b> 1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 3.6 & 2.8mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 40m, Smart IR, IP67, DC12V		4,100,000
27	DH-HAC-HFW1200THP-A <b>NEW Product</b> 2MP HDCVI IR Bullet Camera 1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 3.6mm fixed lens (2.8mm, 6mm Optional), Built-in mic HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 80m, Smart IR, IP67, DC12V		5,350,000
28	DH-HAC-HFW1200DP 1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P DWDR, Day/Night(ICR), AWB, AGC, HLC, BLC, 2D-DNR HD and SD output switchable, 3.6mm fixed lens Max. IR LEDs length 80m, Smart IR, IP67, DC12V		6,100,000
29	DH-HAC-HFW1200BP 1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P DWDR, Day/Night(ICR), AWB, AGC, HLC, BLC, 2D-DNR HD and SD output switchable, 3.6mm fixed lens Max. IR LEDs length 50m, Smart IR, IP67, DC12V		5,650,000
30	DH-HAC-HFW1200SP 1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 3.6mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 30m, Smart IR, IP67, DC12V		4,400,000
31	DH-HAC-HFW1200SLP 1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 3.6mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 30m, Smart IR, IP67, DC12V		3,700,000
32	DH-HAC-HFW1200TP 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 3.6mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 25m, Smart IR, IP67, DC12V		4,200,000
33	DH-HAC-HFW1200TP-A 1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 3.6mm fixed lens, Built-in mic HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 30m, Smart IR, IP67, DC12V		4,600,000
34	DH-HAC-ME1200BP-PIR 2MP HDCVI MotionEye Camera, 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 2.8mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR 10m/110°detecting range/angle HD and SD output switchable, OSD Menu Max. IR length 20m, Smart IR, IP67, DC12V		5,100,000
35	DH-HAC-HUM1220AP 2MP HDCVI MotionEye Camera, 1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 2.8mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR 12m/100°detecting range/angle Two level(jumper) detection sensitivity adjustable Built-in tamper switch, DC12V		6,600,000
36	DH-HAC-HUM3201B 1/2.8" 2Megapixel CMOS(Starlight), 25/30fps@1080P & @720P 2.8mm fixed lens HD and SD output switchable, Support OSD Menu WDR(120dB), Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR, DC12V		8,000,000
37	<b>Cooper Series</b> DH-HAC-B2A21P 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 3.6mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 20m, Smart IR, IP67, DC12V, Casing: Aluminium		3,500,000
38	<b>Cooper Series</b> DH-HAC-B1A21P 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 3.6mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 20m, Smart IR, IP67, DC12V, Casing: Plastic		2,900,000
39	DH-HAC-HDW2802TP-A 4K Starlight HDCVI IR Eyeball Camera, 1/2" Progressive Scan CMOS 15fps@4K, 20fps@6MP, 25/30fps@4MP, 3.6mm fixed lens Max Aperture: F1.6 WDR(120dB), Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR Max. 4K resolution, HD/SD switchable, 1CH Audio In, built-in mic Max. IR length 50m, Smart IR, IP67, DC12V±30%		12,500,000

**توجه:** دستگاه های جدید XVR(به جز دستگاه های ستاره دار)، دوربین هایی که میکروفن داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
40	DH-HAC-HDW2601TP-Z-A 6MP WDR HDCVI IR Eyeball Camera, 1/2.9" Progressive Scan CMOS 20fps@6MP, 25/30fps@4MP, 2.7-13.5mm motorized lens Max Aperture: F1.3 WDR(120dB), Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR Max. 6MP resolution, HD/SD switchable, 1CH Audio In, built-in mic Max. IR length 60m, Smart IR, IP67, DC12V±30%		17,500,000
41	DH-HAC-HDW2601TP-A 6MP WDR HDCVI IR Eyeball Camera, 1/2.9" Progressive Scan CMOS 20fps@6MP, 25/30fps@4MP 3.6mm fixed lens, Max Aperture: F1.9 WDR(120dB), Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR Max. 6MP resolution, HD/SD switchable, 1CH Audio In, built-in mic Max. IR length 50m, Smart IR, IP67, DC12V±30%		12,000,000
42	DH-HAC-HDW1500SLP 5MP HDCVI IR Eyeball Camera, 1/2.7" 5Megapixel CMOS 20fps@5MP, 25/30fps@4MP/1080P, 3.6mm Fixed Lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 20m, Smart IR, IP67, DC12V		6,300,000
43	DH-HAC-HDBW1400RP-VF 1/3" 4.1Megapixel CMOS , 25/30fps@4MP & @1080P & @720P 2.7-13.5mm Varifocal lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable, OSD Menu Max. IR length 30m, Smart IR, IP67, IK10, DC12V		10,500,000
44	DH-HAC-HDW1400EMP-A 1/3" 4.1Megapixel CMOS , 25/30fps@4MP & @1080P & @720P 3.6mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable, <b>Built-in Mic</b> , OSD Menu Max. IR length 50m, Smart IR, IP67, DC12V		7,600,000
45	DH-HAC-HDW1400EMP 1/3" 4.1Megapixel CMOS , 25/30fps@4MP & @1080P & @720P 3.6mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable, OSD Menu Max. IR length 50m, Smart IR, IP67, DC12V		7,000,000
46	DH-HAC-HDW1400MP 1/3" 4.1Megapixel CMOS , 25/30fps@4MP & @1080P & @720P 3.6mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable, OSD Menu Max. IR length 30m, Smart IR, IP67, DC12V		6,100,000
47	HAC-T2A51P 5MP HDCVI IR Eyeball Camera, 1/2.7" 5Megapixel CMOS 20fps@5MP, 25/30fps@4MP & @1080P 3.6mm & 2.8mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable, Support OSD Menu Max. IR length 20m, IP67, DC12V, Casing: Aluminium		5,900,000
48	HAC-T1A51P 5MP HDCVI IR Eyeball Camera, 1/2.7" 5Megapixel CMOS 20fps@5MP, 25/30fps@4MP, 25/30@1080P 3.6mm and 3.6mm and 2.8mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable, Support OSD Menu Max. IR length 20m, IP67, DC12V, Casing: Plastic		5,200,000
49	DH-HAC-T2A41P 1/2.7" 4Megapixel CMOS, 25/30fps@4MP,25/30fps@1080P 2.8mm fixed lens, HD and SD output switchable Max. IR length 20m, IP67, DC12V, Casing: Aluminium		5,400,000
50	DH-HAC-T1A41P 1/2.7" 4Megapixel CMOS, 25/30fps@4MP,25/30fps@1080P 3.6mm fixed lens, HD and SD output switchable Max. IR length 20m, DC12V, Casing: Plastic		4,700,000
51	DH-HAC-HDW1230MP 2MP Starlight HDCVI IR Eyeball Camera, 1/2.8" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P , 3.6mm Fixed Lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR, IP67, DC12V		4700000
52	DH-HAC-HDBW1220RP-VF 1/2.9" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 2.7-12mm vari-focal lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR, IP67, IK10, DC12V		8,500,000

**توجه:** دستگاه های جدید XVR(به جز دستگاه های ستاره دار)، دوربین هایی که میکروفون داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
53 	DH-HAC-HDW1220EMP-A 1/2.9" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 3.6mm fixed lens, <b>Built-in Mic</b> HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 50m, Smart IR, IP67, DC12V		5,800,000
54	DH-HAC-HDW1220MP 1/2.9" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 2.8 & 3.6mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR, IP67, DC12V		4,300,000
55 <b>NEW Product</b>	DH-HAC-HDBW1200EP 2MP HDCVI IR Dome Camera, 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 2.8mm Fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR, IP67, IK10, DC12V		5,600,000
56	HAC-HDPW1200R 1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 3.6mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR, DC12V		3,600,000
57	DH-HAC-HDW1200SLP 1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 2.8mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 20m, Smart IR, IP67, DC12V		3,250,000
58	DH-HAC-HDW1200LP 2MP HDCVI IR Eyeball Camera, 1/2.7" 2Megapixel CMOS Max 30fps@1080P, 2.1mm fixed lens HD and SD output switchable, Built in Mic, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 3m, Smart IR, IP67, DC12V		6,950,000
59	DH-HAC-HDW1200MP 1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 3.6mm fixed lens HD and SD output switchable, Support OSD Menu Day/Night(ICR), AWB, AGC, BLC, 2D-DNR Max. IR length 30m, Smart IR, IP67, DC12V		3,900,000
60  <b>Metal Case</b> <b>NEW Product</b>	DH-HAC-HDW1200EMP-A 1/2.7" 2Megapixel CMOS, 25/30fps@1080P, <b>Built-in MIC</b> Day/Night(ICR), AWB, AGC, BLC, 2DNR, DWDR 3.6 & 2.8mm fixed lens Max. IR LEDs length 50m, Smart IR, IP67, DC12V		5,550,000
61	HAC-HDW1200TLP-A 2MP HDCVI IR Eyeball Camera, 1/2.7" 2Megapixel CMOS 25/30fps@1080P, Built-in MIC Day/Night(ICR), AWB, AGC, BLC, 2DNR, DWDR 3.6 & 2.8mm fixed lens Max. IR LEDs length 30m, Smart IR, IP67, DC12V		4,400,000
<b>Cooper Series</b>			
62	DH-HAC-T2A21P 1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 2.8mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 20m, Smart IR, IP67, DC12V, Casing: Aluminium		3,500,000
<b>Cooper Series</b>			
63	DH-HAC-T1A21P 1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P <b>2.8mm &amp; 3.6</b> fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 20m, Smart IR, Casing: Plastic, DC12V		2,900,000
64	SD22204I-GC Powerful 4x optical zoom (2.7mm~11mm) Max. 25/30fps@1080P, 50/60fps@720P resolution WDR, Day/Night (ICR), DNR (2D&3D), Auto iris, Auto focus, AWB, AGC, BLC, Max 100°/s pan speed, HD & SD Switchable Up to 300 presets, 5 auto scan, 8 tour, 5 pattern, IP66, IK10, OSD		17,000,000
65	DH-SD59225I-HC-S2 1/2.8" 2Megapixel Exmor R CMOS ( <b>Starlight</b> ) Max 25/30fps @1080P & 20/30/50/60fps @720P Resolution 4.8mm ~ 120mm 25x optical zoom WDR (120db), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Max 400°/s pan speed, 360° endless pan rotation Control over coaxial cable 1-channel BNC HDCVI/CVBS output (switchable) Up to 300 presets, 5 auto scan, 8 tour, 5 pattern Built-in 2/1 Alarm in/out, 1 Audio Input, RS485 IR Distance up to 150m, IP66,OSD		70,000,000

**توجه:** دستگاه های جدید XVR (به جز دستگاه های ستاره دار)، دوربین هایی که میکروفن داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
66 SD59230I-HC	2MP 30x Starlight IR PTZ HDCVI Camera, 1/2.8" Exmor R CMOS Max. 25/30fps @1080P(1920x1080) & 50/60fps @720P Resolution 4.5mm~135mm 30x optical zoom WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Max 400°/s pan speed, 360° endless pan rotation HD and SD switchable Up to 300 presets, 5 auto scan, 8 tour, 5 pattern Audio(in/out) 1 / 1 , Built-in 2/1 Alarm in/out IR Distance up to 150m, IP66,OSD		90,000,000
67 DH-SD49225I-HC	2MP 25x Starlight IR PTZ HDCVI Camera, 1/2.8" STARVIS CMOS Max. 25/30fps @1080P(1920x1080) & 50/60fps @720P Resolution 4.8mm~120mm 25x optical zoom WDR(120dB), Day/Night(ICR), Ultra DNR, HLC, BLC, Auto iris, Auto focus Max 400°/s pan speed, 360° endless pan rotation Up to 300 presets, 5 auto scan, 8 tour, 5 pattern HD and SD switchable, 2/1 Alarm In/Out 1CH Audio In, RS485, IR Distance up to 100m, IP66,OSD		53,200,000
68 DH-XVR1A04	4CH Penta-brid 1080N/720P Real-Time Cooper Recorder H.264 video compression, 4CH: 1/4 Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+1 IP up to 2 MP(20 Mbps)] 1 Audio Input / 1 Audio Output, 1 SATA Port , Up to 8 TB HDMI , VGA ,simultaneous video Output 2*USB 2.0, 10/100 Mbps LAN Interface, P2P Support		7,500,000
69 DH-XVR1B04H	4CH Penta-brid 4M-N/1080P None Real-Time Cooper Recorder H.265+/H.265 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+2 IP up to 6 MP(24 Mbps)], 4CH: 1/4 Playback 1 Audio Input / 1 Audio Output, 1 SATA Port , Up to 6 TB HDMI , VGA ,simultaneous video Output, 2*USB 2.0 10/100 Mbps LAN Interface, P2P Support		9,300,000
70 DH-XVR1A08	8CH Penta-brid 1080N/720P noneReal-Time Cooper Recorder H.264 video compression, 8CH:1/4/9 Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+2 IP up to 5 MP(40 Mbps)] 1 Audio Input / 1 Audio Output, 1 SATA Port , Up to 8 TB HDMI , VGA ,simultaneous video Output, 2*USB 2.0 10/100 Mbps LAN Interface, P2P Support		9,500,000
71 DH-XVR1B08H	8CH Penta-brid 4M-N/1080P None Real-Time Cooper Recorder H.265+/H.265 dual-stream video compression 8CH: 1/4/8 Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+4 IP up to 6 Megapixel(48 Mbps)] 1 Audio Input / 1 Audio Output, 1 SATA Port , Up to 6 TB HDMI , VGA ,simultaneous video Output, 2*USB 2.0 10/100 Mbps LAN Interface, P2P Support		14,500,000
72 XVR4104HS-X1	4 Channel Penta-brid 720P Compact 1U Digital Video Recorder H.265+/H.265 dual-stream video compression, 4CH: 1/4 Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+1 IP up to 2 MP(20 Mbps)] 1 Audio Input / 1 Audio Output, 1 SATA Port , Up to 6 TB HDMI , VGA ,simultaneous video Output, RS485 for PTZ support 2*USB 2.0, 10/100 Mbps LAN Interface, P2P Support		8,300,000
73 XVR4108HS-X1	8 Channel Penta-brid 720P Compact 1U Digital Video Recorder H.265+/H.265 dual-stream video compression 4CH: 1/4 Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+2 IP up to 6 MP(40 Mbps)] 1 Audio Input / 1 Audio Output, 1 SATA Port , Up to 6 TB HDMI , VGA ,simultaneous video Output, RS485 for PTZ support 2*USB 2.0, 10/100 Mbps LAN Interface, P2P Support		10,600,000
74 DH-XVR5104HS-X1	4CH Penta-brid 4MP-N/1080P Non-real Time , 1080N/720P Real-Time Recorder, H.265+/H.265 dual-stream video compression Record Rate: 1st channel 5M-N(1~10fps), other channels 4M-N/1080P(1~15fps); 1080N/720P/960H/, D1/CIF (1~25/30fps), 4CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+2 IP up to 6 MP(24 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out, 1 SATA Port , Up to 6 TB 1*HDMI,1* VGA simultaneous video Output, RS485 for PTZ support 2*USB 2.0, 10/100 Mbps LAN Interface, P2P Support		11,500,000

توجه: دستگاه های جدید XVR(به جز دستگاه های ستاره دار)، دوربین هایی که میکروفن داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.




مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
75 DH-XVR5104HS-4KL-X	<p>4CH Penta-brid 4K Recorder, 4K@7fps,6MP@10fps,5MP@12fps,4MP@15fp,4M-N/1080P/720P@25fps</p> <p>H.265+/H.265 dual-stream video compression, 4CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+2 IP up to 8 MP(24 Mbps)], Support Smart Search and Intelligent Video System 1/1 Audio In/Out, 1 SATA Port , Up to 10 TB 1*HDMI(4K) , 1*VGA ,simultaneous video Output RS485 for PTZ support, 2*USB 2.0 1*10/100 Mbps LAN Interface, P2P Support</p>		16,900,000
76 DH-XVR4108HS-X	<p>8CH Penta-brid 1080N/720P noneReal-Time Recorder H.265 video compression, 8CH: 1/4/9 Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+2 IP up to 6 Megapixel(40 Mbps)]</p> <p>1 Audio Input / 1 Audio Output, 1 SATA Port , Up to 10 TB HDMI , VGA ,simultaneous video Output, RS485 for PTZ support 2*USB 2.0, 10/100 Mbps LAN Interface, P2P Support</p>		10,900,000
77 DH-XVR5108HS-X	<p>8CH Penta-brid 1080P None-Real time Recorder 5M-N@10fps, 4M-N/1080P@15fps, 1080N/720P@25fps H.265+/H.265/H.264+/H.264 dual-stream video compression 8CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+4 IP up to 6 MP(48 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out, 1 SATA Port , Up to 10 TB 1*HDMI, 1*VGA ,simultaneous video Output, RS485 for PTZ support 2*USB 2.0, 1*10/100 Mbps LAN Interface, P2P Support</p>		18,000,000
78 DH-XVR5108H-4KL-X	<p>8CH Penta-brid 4K Recorder, 4K@7fps,6MP@10fps,5MP@12fps,4MP@15fp,4M-N/1080P/720P@25fps</p> <p>H.265+/H.265 dual-stream video compression, 1/4CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+4 IP up to 8 Megapixel(48 Mbps)]</p> <p>Support Smart Search and Intelligent Video System 1/1 Audio In/Out, 1 SATA Port , Up to 10 TB 1*HDMI(4K) , 1*VGA ,simultaneous video Output RS485 for PTZ support, 2*USB 2.0 1*10/100/1000 Mbps LAN Interface, P2P Support</p>		26,100,000
79 DH-XVR1B16H	<p>16CH Penta-brid 4M-N/1080P None Real-Time Cooper Recorder H.265+/H.265 dual-stream video compression 16CH: 1/4/8/16 Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+8 IP up to 6 Megapixel(96 Mbps)]</p> <p>1 Audio Input / 1 Audio Output, 1 SATA Port , Up to 6 TB HDMI , VGA ,simultaneous video Output 1 USB 2 , 1 USB 3, 10/100/1000 Mbps LAN Interface, P2P Support</p>		25,000,000
80 DH-XVR4116HS-X	<p>16CH Penta-brid 1080N/720P NoneReal-Time Recorder H.265/H.264 video compression, 16CH: 1/4/9/16 Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+2 IP up to 6 Megapixel(72 Mbps)]</p> <p>1 Audio Input / 1 Audio Output, 1 SATA Port , Up to 10 TB HDMI , VGA ,simultaneous video Output, RS485 for PTZ support 2*USB 2.0, 10/100 Mbps LAN Interface, P2P Support</p>		21,000,000
81 DH-XVR5116H-X	<p>16CH Penta-brid 1080P None-Real time Recorder 5M-N@10fps, 4M-N/1080P@15fps, 1080N/720P@25fps H.265+/H.265/H.264+/H.264 dual-stream video compression 16CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+8 IP up to 6 Megapixel(96 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out, 1 SATA Port , Up to 10 TB 1*HDMI, 1*VGA ,simultaneous video Output, RS485 for PTZ support 2*USB(1 USB2.0 , 1 USB3.0) 1*10/100/1000 Mbps LAN Interface, P2P Support</p>		29,700,000
82 DH-XVR5216AN-X	<p>16CH Penta-brid 1080P None-Real time Recorder 5M-N@10fps, 4M-N/1080P@15fps, 1080N/720P@25fps H.265+/H.265/H.264+/H.264 dual-stream video compression 16CH Playback, Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+8 IP up to 6 MP(96 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out, 2 SATA Port , Up to 10 TB 1*HDMI, 1*VGA ,simultaneous video Output RS485 for PTZ support, 2*USB(1 USB2.0 , 1 USB3.0) 1*10/100/1000 Mbps LAN Interface, P2P Support</p>		35,300,000

**توجه:** دستگاه های جدید XVR(به جز دستگاه های ستاره دار)، دوربین هایی که میکروفن داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
83 DH-XVR5216AN-4KL-X	<p>16CH Penta-brid 4K Recorder 4K@7fps,6MP@10fps,5MP@12fps,4MP@15fp,4M-N/1080P/720P@25fps H.265+/H.265/H.264+/H.264 dual-stream video compression 16CH Playback, Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+8 IP up to 8 MP(96 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out, 2 SATA Port , Up to 10 TB 1*HDMI(4K), 1*VGA ,simultaneous video Output RS485 for PTZ support, 2*USB(1 USB2.0 , 1 USB3.0) 1*10/100/1000 Mbps LAN Interface, P2P Support</p>		49,800,000
84 DH-XVR5232AN-X	<p>32CH Penta-brid 1080P Recorder 5M-N@10fps, 4M-N/1080P@15fps, 1080N/720P@25fps H.265+/H.265/H.264+/H.264 dual-stream video compression 16CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS)[32 IP up to 6 MP(128 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out, 2 SATA Port , Up to 10 TB 1*HDMI(4K), 1*VGA ,simultaneous video Output RS485 for PTZ support, 2*USB(1 USB2.0 , 1 USB3.0) 1*10/100/1000 Mbps LAN Interface, P2P Support</p>		61,500,000
85 XVR5216A-S2	<p>16CH Penta-brid 4M-N/1080P Non-real Time , 1080N/720P Real-Time Recorder, 4M-N/1080P@15fps , 1080N/720P@25fps H.264+/H.264 dual-stream video compression 1/4/9/16CH Playback, Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+8 IP up to 5 MP(96 Mbps)] Support Smart Search and Intelligent Video System 4/1 Audio In/Out, Alarm in/out 16/3, 2 SATA Port , Up to 16 TB HDMI , VGA ,simultaneous video Output, RS485 for PTZ support 2 USB Ports (1 USB 2.0 , 1 USB 3.0) 10/100/1000 Mbps LAN Interface, P2P Support</p>		3,000,000
86 DH-XVR5432L-X	<p>32CH Penta-brid 4MP-N/1080P Non-real Time , 1080N/720P Real-Time Recorder, H.265+/H.265 dual-stream video compression Record Rate: 1st &amp; 2nd channel 5M-N (1~10fps) , others 4M-N/1080P(1~15fps); 1080N/720P/960H/D1/CIF (1~25/30fps) 1/4/9/16CH Playback, Pentabrid (IP+CVI+AHD+TVI+CVBS)[32 IP up to 8 Megapixel(128Mbps)] Two Way talk(1 Mic In, 1 Mic Out), 16 Alarm IN / 6 Alarm Out 4 SATA Port , Up to 10 TB, 1 e-SATA Portm, 2 HDMI, 1 VGA, 1 TV Supports HDMI2 for spot output RS485 , RS232, RS422, 2 USB 3.0, 1 USB 2.0 10/100/1000 Mbps LAN Interface, P2P Support Intelligent Video System(First 16 channels support Tripwire &amp; Intrusion; First 2 channels support Object Abandoned &amp; Missing)</p>		93,000,000
87 DH-XVR5832S-X	<p>32 Channel Penta-brid 1080P 2U Digital Video Recorder H.265+/H.265 dual-stream video compression 1/4/9/16CH Playback, Pentabrid (IP+CVI+AHD+TVI+CVBS)[32 IP up to 8 Megapixel(128Mbps)] 16 Audio IN / 1 Audio Out, 16 Alarm IN / 6 Alarm Out 8 SATA Port , Up to 10 TB, 1 e-SATA Port, 2 HDMI, 1 VGA, 1 TV RS485 , RS232, RS422, 2 USB 3.0, 2 USB 2.0 2 LAN Interface 10/100/1000 Mbps First 16 channels support Tripwire &amp; Intrusion; First 2 channels support Object Abandoned &amp; Missing, P2P Support</p>		108,000,000
88 PFT2100	<p>HDMI-HDCVI Converter *Input HDMI video signal, self-adaptive output HDCVI signal *HDMI support mode, 1024*768@60Hz, 1280*720@50/60Hz, 1280*1024@60Hz,1600*1200@60Hz, 1920*1080@50/60Hz *HDCVI output format, 720P/50, 720P/60, 1080P/25, 1080P/30 *Output Cable Length 1080P: 75-5 coaxial cable support 300m/720P: 75-5 coaxial cable support 500m, Power:DC12V</p>		9,100,000
89 TP2105	<p>HDCVI Video Converter real time non-compression transmission *Input: 1*HDCVI (BNC) *Output: 1*HDCVI (BNC), 1*CVBS (BNC), 1*HDMI, 1*VGA *1080p/720p: 75-5 coaxial support 100m Input Transmission Distance *1080p/720p: 75-5 coaxial support 100m HDCVI Output Transmission Distance *Support 2 dial switches and indicate 4 Baud rate: 2400b/s, 4800b/s, 9600b/s and 115200b/s, RS485</p>		9,700,000

**توجه:** دستگاه های جدید XVR(به جز دستگاه های ستاره دار)، دوربین هایی که میکروفون داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.



مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
90 PFM801	<p>*1 Channel HDCVI Transmission Signal            *720P, 400M(max); 1080P, 200M(max)Transmission Distance            *Input voltage DC24-36V, can provide DC12V8W(max) power supply to remote cameras            *Use single UTP (CAT-5E and CAT-6) real-time transmit 1-ch HD video signal and 1-ch DC power            *Excellent anti-thunder, anti-static and anti-interference capabilities            *Compatible with HDCVI/TVI/AHD format</p>		1,200,000
91 DH-PFM900-E	<p>4" IPS screen and QWERTY flip keyboard with 45keys            Support H.264/H.265 HD decoding protocol            Support IP,HDCVI/AHD/TVI/CVBS            Support IP configuration via Onvif protocol            Support audio and RS485 control            Support TDR network cable test and digital multi-meter function            Support PoE+, DC12V/2A power out;            Replaceable 7.4V/22.2Wh polymer lithium ion battery , which can last 8 hours for normal use;            Compatible with more than 30 PTZ protocols(Pelco-D/P, Samsung, Panasonic, Lilin, Yaan,...)            Dual LED flashlight</p>		60,000,000
92 DH-PFM905-E	<p>4" IPS display, 800*480 resolution, 16.7M colors            Support HDCVI/AHD/TVI/CVBS            Support RS485 PTZ control            Support audio test and digital multi-meter function            Support DC12V/1A power out            Dual LED torch light            Replaceable 7.4V/10.4Wh polymer lithium battery , which can last 5 hours for normal use</p>		31,000,000

