

مدل	مشخصات	تصویر	قیمت(ریال)
1 - NORMA-221ILF	<p>1/2.9" Sony Image Sensor 20fps@2.1MP 1920 (H) * 1080 (V) 3.6mm 3MegaPixel Fixed Lens 15~20m IR Distance - 24 LED H264+ / Mjpeg Comprssion Dual Stream - DWDR - Mechanical ICR 3DNR - AGC - BLC - 1/1 Audio in & out IP66 - 12VDC</p>		6.200.000
2 - HELIX-222ILF	<p>1/2.9" Sony Image Sensor 30fps@2.1MP 1920 (H) * 1080 (V) 3.6mm 3MegaPixel Fixed Lens 40~50m IR Distance - Power Array H265+ / H264+ / Mjpeg Comprssion Tri Stream - DWDR - Mechanical ICR 3DNR - AGC - BLC - 1/1 Audio in & out IP66 - 12VDC VCA Detection : Face Detection - Line Crossing - Intrusion - People Counting - Object Abandoned - Object Missing - Density Detection - Crossing The Fence - Loitering Detection - Retrograde Detection</p>		8.900.000
3 - CAPRINA-422ILF(P)	<p>1/3" CMOS Image Sensor 30fps@4.1MP 2560 (H) * 1440 (V) 3.6mm 4MegaPixel Fixed Lens 60m IR Distance - 4 Array H265+ / H264+ / Mjpeg Comprssion Tri Stream - WDR - Mechanical ICR 3DNR - AGC - BLC - 1/1 Audio in & out IP66 - 12VDC/POE VCA Detection : Face Detection - Line Crossing - Intrusion - People Counting - Object Abandoned - Object Missing - Density Detection - Crossing The Fence - Loitering Detection - Retrograde Detection</p>		11.500.000
4 - PARSIS-221ILF	<p>1/2.9" Sony Image Sensor 20fps@2.1MP 1920 (H) * 1080 (V) 3.6mm 3MegaPixel Fixed Lens 25~30m IR Distance - 36 LED H264+ / Mjpeg Comprssion Dual Stream - DWDR - Mechanical ICR 3DNR - AGC - BLC - 1/1 Audio in & out IP66 - 12VDC</p>		6.400.000
5 - NARSIS-222ILF(P)	<p>1/2.9" Sony Image Sensor 30fps@2.1MP 1920 (H) * 1080 (V) 3.6mm 3MegaPixel Fixed Lens 40~50m IR Distance - Power Array H265+ / H264+ / Mjpeg Comprssion Tri Stream - WDR - Mechanical ICR 3DNR - AGC - BLC - 1/1 Audio in & out IP66 - 12VDC / POE VCA Detection : Face Detection - Line Crossing - Intrusion - People Counting - Object Abandoned - Object Missing - Density Detection - Crossing The Fence - Loitering Detection - Retrograde Detection</p>		8.700.000
6 - AVILON-422ILV	<p>1/3" CMOS Image Sensor 30fps@4.1MP 2560 (H) * 1440 (V) 2.8 ~ 12mm 4MegaPixel Varifocal Lens 40 ~ 50m IR Distance H265+ / H264+ / Mjpeg Comprssion Tri Stream - WDR - Mechanical ICR 3DNR - AGC - BLC - 1/1 Audio in & out IP66 - 12VDC VCA Detection : Face Detection - Line Crossing - Intrusion - People Counting - Object Abandoned - Object Missing - Density Detection - Crossing The Fence - Loitering Detection - Retrograde Detection</p>		13.500.000

7 - LENSI-222ILF	<p>1/2.9" Sony Image Sensor 30fps@2.1MP 1920 (H) * 1080 (V) 3.6mm 3MegaPixel Fixed Lens 40~50m IR Distance - Power Array H265+ / H264+ / Mjpeg Comprssion Tri Stream - WDR - Mechanical ICR 3DNR - AGC - BLC - 1/1 Audio in & out IP66 - 12VDC VCA Detection : Face Detection - Line Crossing - Intrusion - People Counting - Object Abandoned - Object Missing - Density Detection - Crossing The Fence - Loitering Detection - Retrograde Detection</p>		8.200.000
8 - ONR-3104-4K	<p>4ch IP Camera Input H265/H264 Codec Decoding Max 48Mbps Incoming Bandwidth Up to 5 MP Resolution For Preview & Playback 4ch @ 1080P Decoding Performance HDMI(4K)/VGA Simultaneous Video Output Intelligent Function : 1ch Face Detection or Intrusion Detection Support 1 SATA Up to 8TB - 2 USB Port - Two Way Talk 1*10/100Mbps Network Card - P2P Support</p>		10.900.000
9 - ONR-3108-4K	<p>8ch IP Camera Input H265/H264 Codec Decoding Max 60Mbps Incoming Bandwidth Up to 5 MP Resolution For Preview & Playback 4ch @ 1080P Decoding Performance HDMI(4K)/VGA Simultaneous Video Output Intelligent Function : 1ch Face Detection or Intrusion Detection Support 1 SATA Up to 8TB - 2 USB Port - Two Way Talk 1*10/100Mbps Network Card - P2P Support</p>		12.500.000
10 - ONR-3108-P-4K	<p>8ch IP Camera Input - 4 PoE Port H265/H264 Codec Decoding Max 60Mbps Incoming Bandwidth Up to 5 MP Resolution For Preview & Playback 4ch @ 1080P Decoding Performance HDMI(4K)/VGA Simultaneous Video Output Intelligent Function : 1ch Face Detection or Intrusion Detection Support 1 SATA Up to 8TB - 2 USB Port - Two Way Talk 1*10/100Mbps Network Card - P2P Support</p>		19.000.000
11 - ONR-3108-8P-4K	<p>8ch IP Camera Input - 8 PoE Port H265/H264 Codec Decoding Max 60Mbps Incoming Bandwidth Up to 5 MP Resolution For Preview & Playback 4ch @ 1080P Decoding Performance HDMI(4K)/VGA Simultaneous Video Output Intelligent Function : 1ch Face Detection or Intrusion Detection Support 1 SATA Up to 8TB - 2 USB Port - Two Way Talk 1*10/100Mbps Network Card - P2P Support</p>		24.000.000
12 - ONR-3116-4K	<p>16ch IP Camera Input H265/H264 Codec Decoding Max 80Mbps Incoming Bandwidth Up to 5 MP Resolution For Preview & Playback 4ch @ 1080P Decoding Performance HDMI(4K)/VGA Simultaneous Video Output Intelligent Function : 1ch Face Detection or Intrusion Detection Support 1 SATA Up to 8TB - 2 USB Port - Two Way Talk 1*10/100Mbps Network Card - P2P Support</p>		15.500.000

13 - ONR-3216-4K	<p>16ch IP Camera Input H265/H264 Codec Decoding Max 96Mbps Incoming/40Mbps Outgoing Bandwidth Up to 8 MP Resolution For Preview & Playback 4ch @ 1080P Decoding Performance HDMI(4K)/VGA Simultaneous Video Output Intelligent Function : 1ch Face Detection or Intrusion Detection Support 2 SATA Up to 16TB - 2 USB Port - Two Way Talk 1*10/100/1000Mbps Network Card - P2P Support 8/4 Alarm Input & Output - RS485</p>		22.500.000
14 - ONR-3224-4K	<p>24ch IP Camera Input H265/H264 Codec Decoding Max 96Mbps Incoming/40Mbps Outgoing Bandwidth Up to 8 MP Resolution For Preview & Playback 4ch @ 1080P Decoding Performance HDMI(4K)/VGA Simultaneous Video Output Intelligent Function : 1ch Face Detection or Intrusion Detection Support 2 SATA Up to 16TB - 2 USB Port - Two Way Talk 1*10/100/1000Mbps Network Card - P2P Support 8/4 Alarm Input & Output - RS485</p>		24.500.000
15 - ONR-3832-4K	<p>32ch IP Camera Input H265/H264 Codec Decoding Max 200Mbps Incoming Bandwidth Up to 8 MP Resolution For Preview & Playback 16ch @ 1080P Decoding Performance HDMI(4K)/HDMI(1080P)/VGA Simultaneous Video Output Intelligent Function : 1ch Face Detection or Intrusion Detection Support 8 SATA Up to 64TB - 2 USB Port - Two Way Talk 2*10/100/1000Mbps Network Card - P2P Support Support 1 e-SATA - 16/4 Alarm Input & Output - RS485 - RS232</p>		89.500.000
16 - ONR-3864-4K	<p>64ch IP Camera Input H265/H264 Codec Decoding Max 256Mbps Incoming Bandwidth Up to 8 MP Resolution For Preview & Playback 16ch @ 1080P Decoding Performance HDMI(4K)/HDMI(1080P)/VGA Simultaneous Video Output Intelligent Function : 1ch Face Detection or Intrusion Detection Support 8 SATA Up to 64TB - 2 USB Port - Two Way Talk 2*10/100/1000Mbps Network Card - P2P Support Support 1 e-SATA - 16/4 Alarm Input & Output - RS485 - RS232</p>		105.000.000